Hydrologic Model Manager

Short Name	SIRG			
Long Name	Numerical Model of Surface Runoff, Infiltration, River Discharge and Groundwater Flow			
Description				
Model Type	Physically-based, process-oriented, lumped parameter, distributed model			
Model Objectives	To develop a physically based model of runoff for conjunctive use of surface			
•	water and groundwater.			
Agency Office	Department of Civil Engineering, Ajou University, Suwon, South Korea			
Tech Contact	Professor Dong Hoon Yoo			
Model Structure	It is comprised of four modules representing surface runoff, infiltration, river discharge, and ground water flow. Each module is based on theoretical description of physical processes.			
Interception				
Groundwater				
Snowmelt				
Precipitation				
Evapo-transpiration				
Infiltration				
Model Paramters	11 parameters where 4 are for surface runoff, 4 for infiltration, 2 for river discharge, and 1 for groundwater flow.			
Spatial Scale	Grid size			
Temporal Scale	Continuous, limited by the grid size			
Input Requirements	Basin area maps, river cross-sections, rainfall hyetographs, and soil characteristics.			
Computer Requirements	PC with windows			
Model Output	Discharge hydrograph			
Parameter Estimatn Model Calibrtn	Parameters are obtained from physical characteristics and are refined by model calibration.			
Model Testing Verification	Limited testing by comparison with observed discharge values.			
Model Sensitivity	Not reported			
Model Reliabilty	Nor reported			
Model Application	Yang-yang Namdae-chun watershed in northeast Korea			
Documentation	Not available in public domain but it can be obtained from Progessor D. H. Yoo.			
Other Comments				
Date of Submission	5/11/2001 9:12:19 AM			
Developer				
Technical Contact				

tact		